



US009636152B2

(12) **United States Patent**
Daubs et al.

(10) **Patent No.:** **US 9,636,152 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **ROD REDUCER APPARATUS AND METHOD FOR SPINAL CORRECTIVE SURGERY**

(56) **References Cited**

U.S. PATENT DOCUMENTS

- (71) Applicant: **DePuy Synthes Products, Inc.**,
Raynham, MA (US)
- (72) Inventors: **Michael Daubs**, Las Vegas, NV (US);
David S. Rathbun, Gap, PA (US);
Brian Dec, Exton, PA (US)
- (73) Assignee: **DePuy Synthes Products, Inc.**,
Raynham, MA (US)

4,411,259 A	10/1983	Drummond	
5,020,519 A	6/1991	Hayes et al.	
5,364,397 A	11/1994	Hayes et al.	
5,584,831 A *	12/1996	McKay	A61B 17/7005
			606/260
5,616,143 A	4/1997	Schlapfer et al.	
5,720,751 A	2/1998	Jackson	
5,782,830 A	7/1998	Farris	
5,899,901 A	5/1999	Middleton	

(Continued)

- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

DE	4238339	5/1994
EP	1574175	9/2005

(Continued)

(21) Appl. No.: **14/854,424**

(22) Filed: **Sep. 15, 2015**

(65) **Prior Publication Data**

US 2016/0000479 A1 Jan. 7, 2016

Related U.S. Application Data

- (62) Division of application No. 13/139,373, filed as application No. PCT/US2009/006433 on Dec. 8, 2009, now Pat. No. 9,161,788.
- (60) Provisional application No. 61/138,392, filed on Dec. 17, 2008.
- (51) **Int. Cl.**
A61B 17/70 (2006.01)
- (52) **U.S. Cl.**
CPC **A61B 17/7086** (2013.01); **A61B 17/7085** (2013.01)
- (58) **Field of Classification Search**
CPC A61B 17/7085; A61B 17/7086
USPC 606/86 A
See application file for complete search history.

Primary Examiner — Ellen C Hammond

Assistant Examiner — Stuart S Bray

(74) *Attorney, Agent, or Firm* — Baker & Hostetler LLP

(57)

ABSTRACT

Spinal rod reduction apparatuses, systems, and methods are provided. In various examples, a rod reduction apparatus includes a first threaded member including an engagement feature configured to selectively anchor the first threaded member to the implantable screw assembly. A second threaded member is configured to threadably engage with the first threaded member. The second threaded member is axially movable with respect to the first threaded member with rotation of the second threaded member. A spinal rod urging member is axially movable with the second threaded member. The urging member includes a bearing surface that is configured to selectively abut the spinal rod and selectively urge the spinal rod toward the implantable screw assembly with rotation of the second threaded member in a first rotational direction.

19 Claims, 11 Drawing Sheets

